

NOTES:

1. Substrate
2. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACES
3. COATING (APPLY ACROSS COATING APERTURE)

S1: Ravg \geq 95% @ 400 - 690nm @ 0° AOI
Tavg \geq 90% @ 750 - 1200nm @ 0° AOI




S2: AR Coating: Ravg $<$ 1.0% @ 700 - 1150nm @ 0° AOI

4. FINE GRIND SURFACE



5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE

6. RoHS COMPLIANT

**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2	 Edmund Optics®			
SHAPE	PLANO	PLANO				
SURFACE FLATNESS	4 - 6λ	4 - 6λ	THIRD ANGLE PROJECTION		TITLE	35 x 35mm, 0° AOI, COLD MIRROR
SURFACE QUALITY	80-50	80-50			DWG NO	64439
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	SHEET 1 OF 1	