

TECHSPEC® 0.25X MercuryTL™ Liquid Lens Telecentric Lens



0.25X MercuryTL™ Liquid Lens Telecentric Lens



Stock #73-699 NEW 14 In Stock

-

1

+

A\$3,840^{.00}

ADD TO CART

Volume Pricing	
Qty 1+	A\$3,840.00 each
Need More?	Request Quote

Product Downloads

SPECIFICATIONS

General

Mercury Series

Series:

MercuryTL™

Note:

Type:

Telecentric Lens	
Liquid Lens Focusable	Special Type of Lens:
Physical & Mechanical Properties	
155.20	Length excluding Threads (mm):
48.00	Maximum Diameter (mm):
266	Weight (g):
Optical Properties	
25.6mm	Horizontal Field of View, 1/2" Sensor:
19.2mm	Horizontal Field of View, 1/3" Sensor:
<0.035	Typical Telecentricity @ 588nm (°):
<0.040	Typical Distortion @ 588nm (%):
0.25X	Primary Magnification PMAG:
0.25	Telecentric Lens Magnification:
91 - 173	Working Distance (mm):
28.8 x 21.6	FOV @ Max Sensor Format, H x V (mm):
f/10	Aperture (f/#):
±8.2 at f/10 (20% @ 20 lp/mm)	Depth of Field (mm):
VS	Wavelength:
Sensor	
1/2"	Maximum Sensor Format:
Threading & Mounting	
C-Mount	Mount:
Regulatory Compliance	
View	Certificate of Conformance:

PRODUCT DETAILS

- Liquid Lens for Extended Depth of Field Telecentric Lens
 - Up to 2.3 MegaPixels, 4.5µm Pixel Size Sensors
 - Up to 2/3", C-Mount Telecentric Lens
 - Magnification from 0.15X to 0.75X
- TECHSPEC® MercuryTL™ Liquid Lens Telecentric Lenses combine the capabilities of a telecentric lens with the flexibility of a liquid lens. These lenses combine the unique feature of telecentric lenses, eliminating parallax (or perspective) error, with a liquid lens, allowing for the focus to be electronically controlled. This combination provides quick working distance adjustment, while maintaining telecentricity, distortion, and image performance throughout the entire working distance range. TECHSPEC® MercuryTL™ Liquid Lens Telecentric Lenses are ideal for gauging, measurement, and placement applications where quick depth of field adjustment is required.
- As the liquid lens is used to focus the telecentric lens, its curvature changes. As its curvature changes, there will be small changes in the ray angles in the rear of the lens (incident on the image sensor). As a result, there are small field of view changes over the working distance range as the liquid lens refocuses the lens. However, the front (object space) ray angles are unaffected by the liquid lens changing curvature, allowing the telecentric lens to maintain telecentricity over the entire working distance range.
- Note:** Hirose cables and [Liquid Lens Driver](#) sold separately.

TECHNICAL INFORMATION



