

TECHSPEC® 0.5X, 110mm WD, In-Line CompactTL™ Telecentric Lens



110mm WD, 0.5X, In-Line Version (Left) and VIS Version (Right)



Stock #67-303 **14 In Stock**

⊖ 1 ⊕ **A\$772⁰⁰**

ADD TO CART

Volume Pricing	
Qty 1+	A\$772.00 each
Need More?	Request Quote

Product Downloads

General

CompactTL™ Series **Product Family:**
 Edmund Optics® **Manufacturer:**
 Telecentric Lens **Type:**
Compatible Light Guide/Source:
 1/4" (0.312") and 1/8" (0.187")

In-Line Illumination **Type of Illumination:**

Physical & Mechanical Properties

Fixed **Iris Option:**

170.00 **Length (mm):**

170.00 **Length excluding Threads (mm):**

40.00 **Maximum Diameter (mm):**

193 **Weight (g):**

Optical Properties

17.6mm **Horizontal Field of View, 2/3" Sensor:**

12.8mm **Horizontal Field of View, 1/2" Sensor:**

9.6mm **Horizontal Field of View, 1/3" Sensor:**

11.00 **Maximum Image Circle (mm):**

0.027 **Numerical Aperture NA, Object Side:**

±1 **Working Distance Tolerance (mm):**

5 (5) **Number of Elements (Groups):**

0.064 **Typical Telecentricity @ 588nm (°):**

0.0202 **Typical Distortion @ 588nm (%):**

0.5X **Primary Magnification PMAG:**

0.50 **Telecentric Lens Magnification:**

110 **Working Distance (mm):**

17.6 x 13.2 **FOV @ Max Sensor Format, H x V (mm):**

f/9.3 **Aperture (f/#):**

M4 MgF₂ **Coating:**

±1.9mm (20% @ 20 lp/mm) **Depth of Field (mm):**

0.5X **Magnification:**

VIS **Lens Wavelength Range:**

Sensor

2/3" **Maximum Sensor Format:**

4.50 **Pixel Size (µm):**

Threading & Mounting

M37 x 0.75 (Female) **Filter Thread:**

C-Mount **Mount:**

Regulatory Compliance

[Compliant](#) **RoHS 2015:**

[View](#) **Certificate of Conformance:**

[Compliant](#) **REACH 241:**

Product Details


- 2/3", C-Mount Telecentric Lens
- Up to 2.3 MegaPixels, 4.5µm Pixel Size Sensors
- Small Telecentric Lens with Coaxial Illumination Options

TECHSPEC® CompactTL™ Telecentric Lenses are designed for applications with tight space constraints due to their ultra-compact design. These lenses feature a 2/3" sensor format and a variety of different working distance and magnification options. From single unit to high volume implementation, these lenses provide a great price to performance ratio. TECHSPEC® CompactTL™ Telecentric Lenses are perfect for integration into gauging systems due to their excellent telecentricity and low distortion. The fixed iris and lockable focus make these lenses ideal for implementation into factory floors and assembly lines, as they will remain fixed over time.


Technical Information




#67-303, 0.5X, 110mm WD, In-Line CompactTL™ Telecentric Lens, Distortion Plot




#67-303, 0.5X, 110mm WD, In-Line CompactTL™ Telecentric Lens, Relative Illumination Plot



#67-303, 0.5X, 110mm WD, In-Line CompactTL™ Telecentric Lens, Telecentricity Plot



#67-303, 0.5X, 110mm WD, In-Line CompactTL™ Telecentric Lens, Modulated Transfer Function (MTF) Plot, 110mm Working Distance, f9.3



;