

**TECHSPEC® 25mm Dia -1.00λ Aberration, Spherical Aberration Plate**



Spherical Aberration Compensation Plates

Stock **#66-760** **5 In Stock**

⊖ 1 ⊕ **A\$995<sup>20</sup>**

**ADD TO CART**

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1+         | <b>A\$995.20</b> each         |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

**General**

Specialty Window **Type:**  
Glass **Type of Window:**

**Physical & Mechanical Properties**

21.25 **Clear Aperture CA (mm):**  
25.00 +0.00/-0.25 **Diameter (mm):**

|                      |                                            |
|----------------------|--------------------------------------------|
| 4.00 ±0.20           | <b>Thickness (mm):</b>                     |
| <1                   | <b>Parallelism (arcmin):</b>               |
| +0.00/-0.25          | <b>Dimensional Tolerance (mm):</b>         |
| Protective as needed | <b>Bevel:</b>                              |
| >85                  | <b>Clear Aperture (%):</b>                 |
| Fine Ground          | <b>Edges:</b>                              |
| 0.21                 | <b>Poisson's Ratio:</b>                    |
| 82                   | <b>Young's Modulus (GPa):</b>              |
| 610.00               | <b>Knoop Hardness (kg/mm<sup>2</sup>):</b> |

## Optical Properties

|                       |                                             |
|-----------------------|---------------------------------------------|
| Uncoated              | <b>Coating:</b>                             |
| <a href="#">N-BK7</a> | <b>Substrate:</b> <input type="checkbox"/>  |
| 1.516                 | <b>Index of Refraction (n<sub>d</sub>):</b> |
| 60-40                 | <b>Surface Quality:</b>                     |
| 64.17                 | <b>Abbe Number (v<sub>d</sub>):</b>         |
| -1.00λ ±N16 @ 587nm   | <b>Aberration:</b>                          |
| 350 - 2200            | <b>Wavelength Range (nm):</b>               |

## Material Properties

|                                           |                                                                   |
|-------------------------------------------|-------------------------------------------------------------------|
| 2.51                                      | <b>Density (g/cm<sup>3</sup>):</b>                                |
| 7.1 (-30 to +70°C)<br>8.3 (+20 to +300°C) | <b>Coefficient of Thermal Expansion CTE (10<sup>-6</sup>/°C):</b> |

## Regulatory Compliance

|                      |                                    |
|----------------------|------------------------------------|
| <a href="#">View</a> | <b>Certificate of Conformance:</b> |
|----------------------|------------------------------------|

### Need different specs or modifications?

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

## Product Details

- Precision N-BK7 Substrate
- Optimized for Use in Collimated Light with Small Fields of View
- Transmitted Wave Front Accurate to N16

Many optical systems experience some level of spherical aberrations which result in a loss of image quality and overall system performance. Our line of TECHSPEC® Spherical Aberration Compensation Plates are designed to compensate and correct known amounts of spherical aberration at the specified wavelengths. The aberration plates should be used in collimated space and placed near a pupil. They are excellent for correcting spherical aberrations in systems that have small fields of view.

Spherical Aberration Compensation Plates can be combined to induce the desired amount of compensatory spherical aberration. Negative sign plates create over corrected spherical aberration. Positive plates create under corrected spherical aberration.

**Note:** The arrow on the spherical aberration compensation plates points in the direction of light travel.

## Technical Information



## Compatible Mounts

---