

**TECHSPEC® 25mm Thick Inner Single Optic Mount**



TECHSPEC Multi-Element Inner Single Optic Mounts

Stock **#38-758** **7 In Stock**

A\$65<sup>00</sup>

**ADD TO CART**

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-4        | A\$65.60 each                 |
| Qty 5+         | A\$62.40 each                 |
| Need More?     | <a href="#">Request Quote</a> |

Product Downloads

**General**

Fixed **Type:**

Optic Mount (Fixed) **Function:**

**Physical & Mechanical Properties**

23 **Total Length (mm):**

**Min. Thickness of Compatible Optics (mm):**

1.0

**Max. Thickness of Compatible Optics (mm):**  
17.0

**Clear Aperture CA (mm):**  
22.0

**Construction:**  
Matte Black Anodized Aluminum (6061-T6)

**Edge Thickness of Compatible Optics (mm):**  
17.0

## Threading & Mounting

**Thread Type:**  
M29 x 0.75

**Diameter of Compatible Optics (mm):**  
25.0

## Regulatory Compliance

**RoHS 2015:**  
[Compliant](#)

**Certificate of Conformance:**  
[View](#)

**Reach 250:**  
[Compliant](#)

## Product Details

- Mounts for a Variety of Optical Component Diameters and Thicknesses
- M29 Outer Diameter Threads Allow Easy Positioning Within [Outer Tubes](#)
- One Retainer Ring and One Delrin Ring are Included
- Click [Here](#) to See How to Use the Multi-Element Tube System Components to Build an Optical System.

TECHSPEC® Multi-Element Inner Single Optic Mounts are designed to mount a variety of optical components. The mounts support optical diameters from 5mm to 25.4mm, and edge thicknesses of 4mm to 17mm. With M29 x 0.75 outer diameter threads, these mounts can be easily positioned along the optical axis of our TECHSPEC® Multi-Element Outer Tubes. TECHSPEC® Multi-Element Inner Single Optic Mounts include one Delrin ring to ensure secure clamping force between the retainer ring and optic without damaging the optic.

**Note:** Our specially designed ME Spanner Wrench ([#13-567](#)) is highly recommended to move Inner Single Optic Mounts back and forth smoothly utilizing a combined metric and English graduated scale. The hollow design enables transmission of output beam while adjusting lens position. Non-scaled ME Spanner Wrench ([#11-046](#)) is also available.