

TECHSPEC[®] 5mm Diameter, S-Mount Thin Optic Mount



Stock #63-940 20+ In Stock

-1+

A\$65²⁰

ADD TO CART

Volume Pricing	
Qty 1-4	A\$65.20 each
Qty 5-9	A\$58.56 each
Qty 10-25	A\$54.40 each
Need More?	Request Quote

Product Downloads

SPECIFICATIONS

General

Type:
Fixed

Type of Optics:

Circular	
	Function:
Optic Mount (Fixed)	
Physical & Mechanical Properties	
	Extension Length (mm):
5.6	
	Total Length (mm):
8.6	
	Outer Diameter (mm):
16.0	
	Clear Aperture CA (mm):
3.8	
	Max. Thickness of Compatible Optics (mm):
3.0	
	Min. Thickness of Compatible Optics (mm):
1.0	
Threading & Mounting	
	Diameter of Compatible Optics (mm):
5.0	
	Thread Type:
S-Mbunt	
Regulatory Compliance	
	RoHS 2015:
Compliant	
	Certificate of Conformance:
View	
	REACH 241:
Compliant	

PRODUCT DETAILS

• Mounts for Simple Lenses, Achromats, Filters, or Reticles


• Designed to Integrate with Any C, S, or T-Mbunt Components





• Optic is Held in Place with Included Retaining Ring

TECHSPEC® C, S, and T-Mount Circular Optic Mounts are designed to mount a variety of circular optical components into C, S, or T-Mbunt compatible systems. An included threaded retainer ring, designed to accept a standard spanner wrench, securely holds the optical component. These circular optic mounts are compatible with a wide variety of Edmund Optics optomechanical components utilizing C, S, or T-Mbunt threads, such as [extension tubes](#) and [kinematic mounts](#). TECHSPEC® C, S, and T-Mount Circular Optic Mounts are threaded for 1" x32TPI, M12 x0.5, or M42 x0.75 mounting, with 30mm, 16mm, and 48mm outer diameters, respectively. These mounts are ideal for creating and personalization of a diverse range of optical systems.


Note: [#56-353](#), [#56-354](#), [#52-933](#), and [#52-292](#) are all 3-part assemblies


TECHNICAL INFORMATION






S-Thread Simple / Thin Lens Mount





S-Thread Simple /Thin Lens Mount



S-Thread Achromat / Thick Lens Mount

