

[See all 102 Products in Family](#)

7.5mm Dia. x 6.6mm FL, Aspheric Condenser Lens, VIS-EXT



Stock **#72-480** **5 In Stock**

[Other Coating Options](#)

1 A\$87²⁰

ADD TO CART

Volume Pricing

Qty 1-10	A\$87.20 each
Qty 11-49	A\$78.40 each
Need More?	Request Quote

Product Downloads

General

Condenser Lens **Type:**

Physical & Mechanical Properties

7.50 +0.0/-0.2 **Diameter (mm):**

≤30 **Centering (arcmin):**

Clear Aperture CA (mm):

6.75

Edge Thickness ET (mm):

1.18

Center Thickness CT (mm):

3.50 ±0.30

Bevel:

Protective as needed

Diameter of Asphere (mm):

7.50

Shape of Back Surface:

Plano

Optical Properties

Effective Focal Length EFL (mm):

6.60

Numerical Aperture NA:

0.57

Back Focal Length BFL (mm):

4.30

Substrate:

H-K51

Focal Length Tolerance (%):

±5

Coating:

VIS-EXT (350-700nm)

Coating Specification:

R_{avg} <0.5% @ 350 - 700nm

Surface Quality:

80-50 (typical)

f#:

0.88

Radius R₂ (mm):

∞

Wavelength Range (nm):

350 - 700

Conjugate Distance:

Infinite

Regulatory Compliance

Certificate of Conformance:

[View](#)

Product Details

- Molded Illumination Lenses
- Aspheric or Spherical Designs
- High Numerical Apertures

Condenser Lenses are molded lenses designed for illumination applications. Featuring large apertures and short focal lengths, Condenser Lenses are commonly used in emitter-detector applications, projection applications, or condensing illumination applications such as Koehler Illumination. The Aspheric Condenser Lenses are molded on the aspheric surface and ground and polished on the opposite face, offering superior performance. The Plano-Convex (PCX) Condenser Lenses are molded on both surfaces, offering excellent value.

Technical Information



