

[See all 12 Products in Family](#)

Belt Driven Stage, Metric Breadboard Mounting Clamps

See More by [Zaber™](#)



Stock **#23-234** **1 In Stock**

-

1

+

A\$73⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	A\$73.60 each
Need More?	Request Quote

Product Downloads

General

Type:	
Metric	
Manufacturer:	
Zaber Technologies Inc.	
Note:	
Sold in Pairs	

Threading & Mounting

Mounting Threads:	
(2) M4, (1) M6 S.H.C.S. Counter Bore Holes	

Regulatory Compliance	
Compliant	RoHS 2015:
View	Certificate of Conformance:
Compliant	Reach 247:

Product Details

- Designed for Use with Most 40mm T-Slot Extrusion Framing Systems and Accessories
- 500mm and 1000mm Long Travel Lengths Available
- Controlled Manually or via RS-232 Serial Interface
- Integrated 400 Counts per Revolution (CPR) Motor Mounted Encoder

Zaber™ T-Slot Extrusion Belt Driven Stages are computer-controlled stages based on a modular, expandable, T-Slot extrusion structure. The stages are compatible and easily integrated with most T-Slot extrusion framing systems. Zaber™ T-Slot Extrusion Belt Driven Stages can be controlled by the [Zaber™ Programmable Joystick Controller](#) (sold separately), a computer using an optional RS-232 or USB data cable, or manually with the knob integrated into the motor unit. The stage mounting platforms include 6XM4 x0.7 mounting holes on a 25mm grid. Each stage features rotary quadrature encoders integrated into the stepper motor, with 400 Counts per Revolution (CPR) encoder resolution. The integrated rotary encoder provides closed-loop control and slip/stall detection and recovery.

Note: 24-48 VDC universal power supply (required), data cables for daisy chaining, and computer interface cables (USB or RS-232) are sold separately as accessories.