

[See all 67 Products in Family](#)

## CW Series to LUCID Triton™ C-Mount Adapter with O-Ring

See More by [LUCID Vision Labs™](#)



#23-669 CW Series to LUCID Triton™ C-Mount Adapter with O-Ring



Stock **#23-669** **20+ In Stock**

A\$84<sup>00</sup>

**ADD TO CART**

### Volume Pricing

Qty 1+	A\$84.80 each
Need More?	<a href="#">Request Quote</a>

### Product Downloads

### General

Thread Adapter **Type:**

### Physical & Mechanical Properties

27.50 **Inner Diameter (mm):**

**Total Length (mm):**

8.30

**Outer Diameter (mm):**

38.00

**Clear Aperture CA (mm):**

24.75

**Construction:**

Black Anodized Aluminum (6061-T6)

**Extension Length (mm):**

6.00

## Sensor

**Pixel Size (µm):**

1.85

## Threading & Mounting

**Mounting Threads:**

Male to Female

**Thread Type:**

C-Mount to T-Mount

## Environmental & Durability Factors

**Environmental Rating:**

IPX7 and IPX9K

## Regulatory Compliance

**Certificate of Conformance:**

[View](#)

## Product Details

- Compact 29 x 29 x 45mm Form Factor
- Global, Rolling, or Polarized CMOS Sensors
- IP67 Protection with Optional Lens Tubes

LUCID Vision Labs Triton™ GigE Power over Ethernet (PoE) Cameras provide exceptional price performance in a compact 29 x 29mm form factor. These cameras are available with Sony's Pregius™ and Starvis™ imaging sensors with up to 24.5 megapixels of resolution, as well as Sony's polarized sensor. Each imaging sensor is actively aligned during manufacturing, ensuring sharp and crisp images even in the corners. Using the accessory IP67 lens tubes (sold separately), LUCID Vision Labs Triton GigE Power over Ethernet (PoE) Cameras can operate in harsh environments where dust or water are present up to IP67 thresholds. Triton cameras are ideal for automotive, process control, and food and beverage applications.