

[See all 77 Products in Family](#)

1/4-20 Mounting Adapter for IDS Imaging USB 3/GigE/PoE Camera - Rev 2

See More by [IDS Imaging Development Systems](#)



1/4-20 Mounting Adapter for IDS Imaging USB 3/GigE/PoE Camera - Rev2, #35-088

Stock **#35-088** **12 In Stock**

⊖ 1 ⊕ **A\$72⁰⁰**

ADD TO CART

Volume Pricing

Qty 1+	A\$72.00 each
Need More?	Request Quote

Product Downloads

General

Camera Accessory **Type:**

Regulatory Compliance

Compliant **RoHS 2015:**

View **Certificate of Conformance:**

REACH 241:

Product Details

- Standard (SE) and Compact (CP) Housing Options Available
- C-Mount with Large Format CMOS Sensors up to 1.1"
- GenICam GigE Vision Compliant
- [IDS Imaging uEye CP/XCP/SE USB3 Cameras](#) Available

IDS Imaging uEye CP/SE GigE Cameras utilize IDS Imaging's [peak SDK platform](#) that supports GenICam and GigE Vision standards for ease of software development and integration. The CP cameras are the industry standard size of 29 x 29 x 29mm and work for almost any application. The SE cameras have a larger housing size of 34 x 44 x 47mm to allow for exceptional heat management and are ideal for noise and heat sensitive applications. IDS Imaging uEye CP/SE GigE Cameras feature a screwable 8-pin Hirose connector for trigger and flash as well as two GPIOs. These cameras are ideal for a variety of applications such as automation, automotive, medical technology, and logistics.
