

[See all 105 Products in Family](#)

IDS IMAGING U3-3046LE-C-HQ, 1/3" USB 3 Color Camera Rev. 1.2

See More by [IDS Imaging Development Systems](#)



IDS Imaging uEye+ USB3 Cameras



Stock #73-670 **1 In Stock**

⊖ 1 ⊕ A\$864⁰⁰

ADD TO CART

Volume Pricing

Qty 1+	A\$864.00 each
Need More?	Request Quote

Product Downloads

Color **Spectrum:**

General

Color Camera **Type:**

U3-3046LE-C-HQ **Model Number:**

Manufacturer:

Camera Series:

uEye+ LE

Physical & Mechanical Properties

Dimensions (mm):

47 x 46 x 25 (excludes connectors and lens mount)

Weight (g):

38

Housing:

Full

Sensor

Image Buffer:

Not Specified

Sensor Format:

1/2.9"

Resolution (Megapixels):

1.57

Frame Rate (fps):

230.00

Pixels (H x V):

1,448 x 1,086

Pixel Size, H x V (µm):

3.45 x 3.45

Sensing Area, H x V (mm):

4.995 x 3.746

Imaging Sensor:

Sony IMX273

Type of Sensor:

Progressive Scan CMOS

Shutter Type:

Global

Pixel Depth:

12 bit

Exposure Time:

0.025ms - 2000ms

Dynamic Range (dB):

70.00

Machine Vision Standard:

USB3 Vision

Electrical

Power Consumption (W):

1 - 2

Hardware & Interface Connectivity

Interface:

USB 3.0

Connector:

USB Type-C

Power Supply:

Power over USB

GPIOs:

N/A

Synchronization:

Hardware Trigger (GPIO); Software Trigger

Interface Port Orientation:

Back Panel (Right Angle)

GPIO Connector Type:

No GPIO Connector Available

Threading & Mounting

Mount:

S-Mount (M12 x 0.5)

Mounting Threads:

1/4-20 with Tripod Mount Adapter [#16-017](#)

Environmental & Durability Factors

Operating Temperature (°C):

0 to +55

Storage Temperature (°C):

-20 to +80

Regulatory Compliance

Product Details

- Standard (SE), Compact (CP), and Ultra Compact (XCP) Housing Options Available
- C-Mount with Large Format CMOS Sensors up to 1.1"
- Up to 20.44MP Resolution with Framerrates up to 396fps

IDS Imaging uEye CP/XCP/SE USB3 Cameras utilize [IDS Imaging's peak SDK platform](#) that supports GeniCam and USB3 Vision standards for easy software development and integration. The CP cameras are the industry standard size of 29 x 29 x 29mm and work for almost any application. The XCP cameras have an ultra-compact size of 29 x 29 x 17mm and are an excellent option for price-sensitive, single-camera applications. The SE cameras have a larger housing size of 34 x 44 x 47mm to allow for exceptional heat management and are ideal for noise and heat-sensitive applications. IDS Imaging uEye CP/XCP/SE USB3 Cameras are ideal for manufacturing, industrial, and automation applications.
